

ULTRA

N TYPE


- Fire Class A
- High Energy Performance
- Strengthened Mechanical Load (5400Pa)
- Advanced Bifacial Efficiency
- 100% Inspection 30years Guarantee (100% TEST MES)
- SMBB Technology Half Cut N Type Cell

SKT620-645M12-132D5

620-645 Watt

210x182mm 16BB 132Cells Double Glass Bifacial
N Type Mono Half Cell PV Module Series

Sunket N Type Linear Warranty



30 Year
87.4% Output
Power guarantee


15 Year
Materials and
workmanship

SUNKET - Solar


SKT620-645M12-132D5

210x182mm 16BB 132Cells Double Glass Bifacial
N Type Mono Half Cell PV Module Series

SUNKET - Solar



Current-Voltage & Power-Voltage Curves (SKT645M12-132D5)



All Dimensions in mm
The above drawing is a graphical representation of the product.

Electrical Characteristics (STC/NMOT)

Module Type	SKT620M12-132D5		SKT625M12-132D5		SKT630M12-132D5		SKT635M12-132D5		SKT640M12-132D5		SKT645M12-132D5	
Test Conditions	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power- Pmax(W)	620	468.2	625	471.9	630	475.7	635	479.4	640	483.2	645	486.9
Open Circuit Voltage - Voc(V)	49.10	46.62	49.30	46.81	49.50	47.00	49.70	47.19	49.90	47.38	50.10	47.57
Short- Circuit Current - Isc(A)	16.07	12.98	16.13	13.03	16.19	13.08	16.25	13.13	16.31	13.18	16.37	13.23
Voltage at Pmax -Vmp(V)	40.76	38.25	40.91	38.42	41.04	38.59	41.18	38.75	41.32	38.92	41.46	39.08
Current at Pmax - Imp(A)	15.21	12.24	15.28	12.28	15.35	12.33	15.42	12.37	15.49	12.42	15.56	12.46
Module Efficiency -ηm(%)	23.00	/	23.10	/	23.30	/	23.50	/	23.70	/	23.90	/
Power Tolerance(W)	（0，+5W）											
Maximum System Voltage(V)	1500Vdc (IEC / UL)											
Maximum Series Fuse Rating (A)	30A											

*STC ： Irradiance 1000W/m², Cell Temperature 25°C, Air Mass 1.5
*NMOT： Irradiance 800W/m², Ambient Temperature 20°C, Air Mass1.5, Wind Speed 1m/s
*Measurement tolerance: ±3%　*Power binning up to: +3%

Mechanical Specifications

External Dimensions	2382x1134x30mm
Weight	32.4kg
Solar Cells	N-Type 16BB 182x105mm (2x66pcs)
Glass	AR Coated 2+2 mm tempered glass
Frame	Anodized aluminum alloy
Junction Box	IP68
Output Cables	4.0mm², 1200mm (+),1200mm (-), length can be customized
Connector	MC4 Compatible
Mechanical Load	Front Side Max. 5400Pa, Rear Side Max. 2400Pa

Bifacial Output Rear Side Power Gain

*Take SKT645M12-132D5 as an example.

Power Gain	5%	10%	20%
Maximum Power- Pmax(W)	677.3	709.5	774.0
Open Circuit Voltage - Voc(V)	50.10	50.10	50.10
Short- Circuit Current - Isc(A)	17.00	17.81	19.42
Voltage at Pmax -Vmp(V)	41.46	41.46	41.46
Current at Pmax - Imp(A)	16.34	17.11	18.67

Temperature Characteristics

Pmax Temperature Coefficient	-0.290%/°C
Voc Temperature Coefficient	-0.250%/°C
Isc Temperature Coefficient	+0.045%/°C
Operating Temperature Range	-40~+85°C
Nominal Operating Cell Temperature(NMOT)	45±2°C

Packing Configuration

Pallet Dimensions	1164x1140x2495mm		
Ways of Transport	40'HQ	13.5m Flatbed Truck	17.5m Flatbed Truck
Pieces per Pallet	37 Pcs	36 Pcs	36 Pcs
Pallets per Container	20 Pallets	16 Pallets	25 Pallets
Pieces per Container	740 Pcs	576 Pcs	900 Pcs

 ©Copyright 2026 Sunket